

Eaton C14G8

Catalog Number: C14G8

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 8 Amps, 80 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH14 Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C14G8
	UPC
	051712589918
EAN	Product Length/Depth
5027590494182	51 mm
Product Height	Product Width
14.3 mm	14.3 mm
Product Weight	Compliances
20.8 g	RoHS Compliant
	CE Marked
	GoST-R
Certifications	
IEC 60269	

defaultTaxonomyAttributeLabel	Resources
Type	Catalogs
fuse	CA134002EN
Application	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
for industrial applications	Bussmann series complete full line catalog no. 1007
for general purpose use	
Amperage Rating	Compliance information
8 A	CE C08G, C08M, etc cylindrical fuselinks
	UKCA C08G, C08M, etc cylindrical fuselinks
Fuse size	Technical data sheets
14 x 51 mm	720115 Cylindrical fuses
Current type	
AC	
Breaking capacity	
80 kA	
Frequency rating - max	
62 Hz	
Frequency rating - min	
45 Hz	
Rated voltage AC	
690 V	
Class	
Class C gL/gG	
Fuse type	
C14G	
Utilization category	
gL/gG (cable protection/equipment protection)	
Fuse indicator	
Other	
Watt losses	
1 W	
Connection	
Ferrule end x ferrule end	
Construction size	
14 mm x 51 mm	
Fuse shape	

Cylindrical

Voltage type

AC

Suitable for

CH14 Modular fuse holder

Material

Ceramic

Mounting method

14 x 51 mm CH Modular fuse holder

Release characteristic

Other

Quantity

10

Voltage rating

690 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia