

# Eaton C14G12

Catalog Number: C14G12

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 12 Amps, 80 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH14 Modular fuse holder



## General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C14G12
	UPC
	051712754361
EAN	Product Length/Depth
5027590493826	51 mm
Product Height	Product Width
14.3 mm	14.3 mm
Product Weight	Warranty
20.3 g	1 year limited
Compliances	Certifications
CE Marked	IEC 60269
GoST-R	
RoHS Compliant	

## Type

fuse

## Application

for industrial applications  
for general purpose use

## Amperage Rating

12 A

## Fuse size

14 x 51 mm

## Current type

AC

## Breaking capacity

80 kA

## Frequency rating - max

62 Hz

## Frequency rating - min

45 Hz

## Rated voltage AC

690 V

## Class

Class C gL/gG

## Fuse type

C14G

## Utilization category

gG (cable protection/equipment protection)

## Fuse indicator

Other

## Watt losses

1.7 W

## Connection

Ferrule end x ferrule end

## Construction size

14 mm x 51 mm

## Fuse shape

## Catalogs

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)[CA134002EN](#)[Bussmann series complete full line catalog no. 1007](#)

## Compliance information

[CE C08G, C08M, etc cylindrical fuselinks](#)[UKCA C08G, C08M, etc cylindrical fuselinks](#)

## Technical data sheets

[720115 Cylindrical fuses](#)

Cylindrical

Voltage type

AC

Suitable for

CH14 Modular fuse holder

Material

Ceramic

Mounting method

14 x 51 mm CH Modular fuse holder

Release characteristic

Other

Quantity

10

Voltage rating

690 V



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)