

Eaton C14G25

Catalog Number: C14G25

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 25 Amps, 80 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH14 Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C14G25
	UPC
	051712754392
EAN	Product Length/Depth
5027590493956	51 mm
Product Height	Product Width
14.3 mm	14.3 mm
Product Weight	Warranty
20.3 g	1 year limited
Compliances	Certifications
CE Marked	IEC 60269
GoST-R	
RoHS Compliant	

defaultTaxonomyAttributeLabel

Type

fuse

Application

for industrial applications
for general purpose use

Amperage Rating

25 A

Fuse size

14 x 51 mm

Current type

AC

Breaking capacity

80 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated voltage AC

690 V

Class

Class C gL/gG

Fuse type

C14G

Utilization category

gG (cable protection/equipment protection)

Fuse indicator

Other

Watt losses

3.3 W

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Fuse shape

Resources

Catalogs

CA134002EN

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[CE C08G, C08M, etc cylindrical fuselinks](#)

[UKCA C08G, C08M, etc cylindrical fuselinks](#)

Technical data sheets

[720115 Cylindrical fuses](#)

Cylindrical

Voltage type

AC

Suitable for

CH14 Modular fuse holder

Material

Ceramic

Mounting method

14 x 51 mm CH Modular fuse holder

Release characteristic

Other

Quantity

10

Voltage rating

690 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia