

Eaton 315NHG2B

Catalog Number: 315NHG2B

Fuse-link, low voltage, 315 A, AC 500 V, NH2, gL/gG, IEC, dual indicator

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	315NHG2B
	EAN
	5027590420587
UPC	Product Length/Depth
051712626170	150 mm
Product Height	Product Width
71 mm	54 mm
Product Weight	Compliances
659 g	CE Marked
	RoHS Compliant
Certifications	
IEC 60269-1	
IEC 60269-2	
DIN 43620	



Electrical data

Amperage Rating

315 A

Voltage rating

500 V

Voltage type

AC

Breaking capacity

120 kA

Class

Class gG/gL

Frequency rating - min

45 Hz

Frequency rating - max

62 Hz

Product specification

Fuse size

NH2

Insulated metal gripping lugs (IMGL)

No

Accessories

Suitable for

SD2-D Single pole NH Fuse base

TD2-D Tripe pole NH Fuse base

Microswitch 170H0235

Microswitch 170H0236

EBH Size 00 to 4 Horizontal fuse switch-disconnectors

Resources

Catalogues

CA134002EN

NH Fuse links, bases and gear

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

Compliance information

UKCA Size 2 NH 500V

Multimedia

[Eaton Bussmann – NH fuse link portfolio](#)

Presentations

[NH Overview Video](#)

Technical data sheets

[10164 NH 500 Volts gG](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia