


Eaton C22M2

Catalog Number: C22M2

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 2 Amps, 80 kA Breaking capacity, class aM, without indicator, compatible with a CH22 Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C22M2
	UPC
	051712667401
EAN	Product Length/Depth
5027590495738	58 mm
Product Height	Product Width
22.2 mm	22.2 mm
Product Weight	Warranty
51 g	1 year limited
Compliances	Certifications
CE Marked	IEC 60269
GoST-R	
RoHS Compliant	

defaultTaxonomyAttributeLabel	Resources
Type	Catalogs
fuse	CA134002EN
Application	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
motor protection for industrial applications	Bussmann series complete full line catalog no. 1007
Amperage Rating	Compliance information
2 A	CE C08G, C08M, etc cylindrical fuselinks
Fuse size	UKCA C08G, C08M, etc cylindrical fuselinks
22 x 58 mm	Technical data sheets
Current type	720115 Cylindrical fuses
AC	
Breaking capacity	
80 kA	
Frequency rating - max	
62 Hz	
Frequency rating - min	
45 Hz	
Rated voltage AC	
690 V	
Class	
Class aM	
Fuse type	
C22M	
Utilization category	
aM (switchgear protection)	
Fuse indicator	
Other	
Watt losses	
0.29 W	
Connection	
Ferrule end x ferrule end	
Construction size	
22 mm x 58 mm	
Fuse shape	

Cylindrical

Voltage type

AC

Suitable for

CH22 Modular fuse holder

Material

Ceramic

Mounting method

22 x 58 mm CH Modular fuse holder

Release characteristic

Other

Quantity

10

Voltage rating

690 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia