

Eaton C10G2

Catalog Number: C10G2

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 2 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CHM Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C10G2
	Model Code
	CYLINDRICAL FUSE 10 x 38 2A GG 500V AC
UPC	EAN
051712754224	5027590493468
Product Length/Depth	Product Height
38 mm	10 mm
Product Width	Product Weight
10 mm	8.2 g
Compliances	Certifications
RoHS Compliant	IEC 60269
CE Marked	
GoST-R	

defaultTaxonomyAttributeLabel	Resources
Type	Catalogs
fuse	CA134002EN
Application	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
for industrial applications	Bussmann series complete full line catalog no. 1007
for general purpose use	
Amperage Rating	Compliance information
2 A	CE C08G, C08M, etc cylindrical fuselinks
	UKCA C08G, C08M, etc cylindrical fuselinks
Fuse size	Technical data sheets
10 x 38 mm	720115 Cylindrical fuses
Current type	
AC	
Breaking capacity	
120 kA	
Frequency rating - max	
62 Hz	
Frequency rating - min	
45 Hz	
Rated voltage AC	
500 V	
Class	
Class C gL/gG	
Fuse type	
C10G	
Utilization category	
gL/gG (cable protection/equipment protection)	
Fuse indicator	
Other	
Watt losses	
0.6 W	
Connection	
Ferrule end x ferrule end	
Construction size	
10 mm x 38 mm	
Fuse shape	

Cylindrical

Voltage type

AC

Suitable for

CHM Modular fuse holder

Material

Ceramic

Mounting method

Holder

Packaging type

Standard

Release characteristic

Other

Quantity

10

Voltage rating

500 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia