

# Eaton C10G16

Catalog Number: C10G16

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 16 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CHM Modular fuse holder



## General specifications

|                                                    |                                         |
|----------------------------------------------------|-----------------------------------------|
| <b>Product Name</b>                                | <b>Catalog Number</b>                   |
| Eaton Bussmann series low voltage cylindrical fuse | C10G16                                  |
|                                                    | <b>Model Code</b>                       |
|                                                    | CYLINDRICAL FUSE 10 x 38 16A GG 500V AC |
| <b>UPC</b>                                         | <b>EAN</b>                              |
| 051712754286                                       | 5027590493437                           |
| <b>Product Length/Depth</b>                        | <b>Product Height</b>                   |
| 38 mm                                              | 10 mm                                   |
| <b>Product Width</b>                               | <b>Product Weight</b>                   |
| 10 mm                                              | 8.2 g                                   |
| <b>Warranty</b>                                    | <b>Compliances</b>                      |
| 1 year limited                                     | CE Marked                               |
|                                                    | GoST-R                                  |
|                                                    | RoHS Compliant                          |
| <b>Certifications</b>                              |                                         |
| IEC 60269                                          |                                         |

| defaultTaxonomyAttributeLabel              | Resources                                                              |
|--------------------------------------------|------------------------------------------------------------------------|
| Type                                       | Catalogs                                                               |
| fuse                                       | CA134002EN                                                             |
| Application                                | eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf |
| for industrial applications                | Bussmann series complete full line catalog no. 1007                    |
| for general purpose use                    |                                                                        |
| Amperage Rating                            | Compliance information                                                 |
| 16 A                                       | CE C08G, C08M, etc cylindrical fuselinks                               |
|                                            | UKCA C08G, C08M, etc cylindrical fuselinks                             |
| Fuse size                                  | Technical data sheets                                                  |
| 10 x 38 mm                                 | 720115 Cylindrical fuses                                               |
| Current type                               |                                                                        |
| AC                                         |                                                                        |
| Breaking capacity                          |                                                                        |
| 120 kA                                     |                                                                        |
| Frequency rating - max                     |                                                                        |
| 62 Hz                                      |                                                                        |
| Frequency rating - min                     |                                                                        |
| 45 Hz                                      |                                                                        |
| Rated voltage AC                           |                                                                        |
| 500 V                                      |                                                                        |
| Class                                      |                                                                        |
| Class C gL/gG                              |                                                                        |
| Fuse type                                  |                                                                        |
| C10G                                       |                                                                        |
| Utilization category                       |                                                                        |
| gG (cable protection/equipment protection) |                                                                        |
| Fuse indicator                             |                                                                        |
| Other                                      |                                                                        |
| Watt losses                                |                                                                        |
| 1.6 W                                      |                                                                        |
| Connection                                 |                                                                        |
| Ferrule end x ferrule end                  |                                                                        |
| Construction size                          |                                                                        |
| 10 mm x 38 mm                              |                                                                        |
| Fuse shape                                 |                                                                        |

Cylindrical

Voltage type

AC

Suitable for

CHM Modular fuse holder

Material

Ceramic

Mounting method

Holder

Release characteristic

Other

Quantity

10

Voltage rating

500 V



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.  
  
All other trademarks are property of their respective owners.



Eaton.com/socialmedia