

# Eaton C14G40

Catalog Number: C14G40

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 40 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH14 Modular fuse holder



## General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C14G40
	UPC
	051712754415
EAN	Product Length/Depth
5027590494076	51 mm
Product Height	Product Width
14.3 mm	14.3 mm
Product Weight	Warranty
20.5 g	1 year limited
Compliances	Certifications
CE Marked	IEC 60269
GoST-R	
RoHS Compliant	

## defaultTaxonomyAttributeLabel

### Type

fuse

### Application

for industrial applications  
for general purpose use

### Amperage Rating

40 A

### Fuse size

14 x 51 mm

### Current type

AC

### Breaking capacity

120 kA

### Frequency rating - max

62 Hz

### Frequency rating - min

45 Hz

### Rated voltage AC

500 V

### Class

Class C gL/gG

### Fuse type

C14G

### Utilization category

gG (cable protection/equipment protection)

### Fuse indicator

Other

### Watt losses

4.75 W

### Connection

Ferrule end x ferrule end

### Construction size

14 mm x 51 mm

### Fuse shape

## Resources

### Catalogs

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[CA134002EN](#)

[Bussmann series complete full line catalog no. 1007](#)

### Compliance information

[UKCA C08G, C08M, etc cylindrical fuselinks](#)

[CE C08G, C08M, etc cylindrical fuselinks](#)

### Technical data sheets

[720115 Cylindrical fuses](#)

Cylindrical

Voltage type

AC

Suitable for

CH14 Modular fuse holder

Material

Ceramic

Mounting method

14 x 51 mm CH Modular fuse holder

Release characteristic

Other

Quantity

10

Voltage rating

500 V



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)