

Eaton 63NHG000B

Catalog Number: 63NHG000B

Eaton Bussmann series low voltage NH Fuse, Live gripping lug, 500V, 63A, 120 kAIC, Combination fuse status indicator, Blade end connection, Class C gL/gG, Square-body with knife blade contact, Metal plated copper contact plate, Ceramic body

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	63NHG000B
	UPC
	051712625845
EAN	Product Length/Depth
5027590485326	79 mm
Product Height	Product Width
51 mm	21 mm
Product Weight	Compliances
119.333 g	RoHS Compliant
	CE Marked
Certifications	
IEC 60269-1	
IEC 60269-2	
DIN 43620	



defaultTaxonomyAttributeLabel	Resources
Type	Catalogs
fuse	CA134002EN
Special features	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
Live gripping lug	NH Fuse links, bases and gear
Application	Bussmann series complete full line catalog no. 1007
industrial	Compliance information
Utilities, Solar, Wind	UKCA NH Size 000, 500V fuse-links
Amperage Rating	CE NH Size 000, 500V fuse-links
63 A	Multimedia
Fitted with:	Eaton Bussmann – NH fuse link portfolio
Metal gripping lugs	Presentations
Fuse size	NH Overview Video
NH000	Technical data sheets
Current type	10164 NH 500 Volts gG
AC	
Breaking capacity	
120 kA	
Frequency rating - max	
62 Hz	
Frequency rating - min	
45 Hz	
Rated switching capacity	
120 kA	
Rated voltage AC	
500 V	
Class	
Class gG/gL	
Fuse type	
Square body with knife blade contact	
Contact material	
Metal plated copper	
Utilization category	
gL/gG (cable protection/equipment protection)	
Interrupt rating	

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Connection

Blade end

Construction

NH000

Construction size

NH000

Fuse shape

Knife blade contacts

Square body

Voltage type

AC

Suitable for

Microswitch 170H0236

EBF Vertical fuse rail

EBV Vertical fuse switch-disconnectors

EBH Size 000 Horizontal fuse switch-disconnectors

Material

Ceramic body

Quantity

3

Voltage rating

500 V